WALLCOLMONOY
HI TEMP BRAZING ALLOYS

NICROBRAZNEWS OCTOBER 2026

Nicrobraz® Tape & Sheet Shelf Life

Shelf Life

Shelf life is measured from the date of manufacture.

Nicrobraz® Tape & Sheet	Shelf Life	Storage Condition
All products	24 months	See storage guidance below

Storage Guidance

- ✓ Keep in a cool, dry area
- ✓ Keep away from direct sunlight and heat sources
- ✓ Store in a sealed container to minimize volatilization of the adhesive
- ✓ Recommended storage temperature is below 27°C (80°F) and above the local dew point

Inspect Before Use

Nicrobraz® Transfer Tape may remain usable beyond the stated shelf life if the adhesive has not dried out.

Confirm that:

- The tape can be separated from the paper backing and plastic
- The tape can be applied to the part satisfactorily
- There is no breakdown of the powder portion of this material.

Beyond the Dated Shelf Life

A shelf life is given for these products and is intended only as a guideline. It is not our intention to indicate that the products will not be usable after that date. Many customers have used these products satisfactorily well beyond the stated shelf life.

We are aware of instances where tape was used after being stored for 20 years or more and still performed satisfactorily. While this does not guarantee performance in every case, these products may remain usable well beyond the stated shelf life when properly stored.

For complete handling and safety information, refer to the applicable SDS before use.

© 2026 Wall Colmonoy | wallcolmonoy.com
Alloy Products: (USA) wcc@wallcolmonoy.com | (UK) alloyproductsales@wallcolmonoy.co.uk

For more information, please contact:

WORLD HEADQUARTERS

WALL COLMONOY CORP. (USA)

101 W. Girard
Madison Heights, MI 48071
Tel: 248-585-6400
Email: wcc@wallcolmonoy.com

EUROPEAN HEADQUARTERS

WALL COLMONOY LTD. (UK)

Alloy Industrial Estate
Pontardawe Swansea SA8 4HL
Tel: +44 (0) 1792 862287
Email: alloyproductsales@wallcolmonoy.co.uk

About Wall Colmonoy and Brazing
The Pioneers and Today's Leading Experts

Wall Colmonoy joins parts for high-temperature and corrosion applications using Nicrobraz®, Niferobraz®, and CuBraz™ brazing filler metals and brazing aids.

The pioneer of high-temperature brazing, Wall Colmonoy's expert brazing engineer, Bob Peaslee, invented a new brazing technology involving nickel-based filler metals and hydrogen atmosphere furnaces in 1950. As a result, the new filler metal, Nicrobraz®, was created.

Today, Nicrobraz®, Niferobraz®, and CuBraz™ brazing filler metals are used in a variety of industries including aerospace, oil & gas, steel, energy, food, automotive, rail and defense, meeting AWS, AMS, G.E., Honeywell, Pratt & Whitney and Rolls-Royce specifications. Nicrobraz® products are available as powder, paste, transfer tape, rods, and sheets in a full range of sizes and specifications. Wall Colmonoy also custom formulates brazing filler metals to meet customer specific requirements.

Copyright © 2026 by Wall Colmonoy Corporation. All rights reserved.
No part of this work may be published, translated or reproduced in any form or by any means, or incorporated into any information retrieval system, without the written permission of the copyright holder. Permission requests should be addressed to: Marketing Communications, marketing@wallcolmonoy.com

Disclaimer
Although the information presented in this work is believed to be reliable, this work is published with the understanding that Wall Colmonoy and the authors are supplying general information and are not attempting to render or provide engineering or professional services. Neither Wall Colmonoy nor any of its employees make any warrant, guarantee, or representation, whether expressed or implied, with respect to the accuracy, completeness or usefulness of any information, product, process or apparatus discussed in this work; and neither Wall Colmonoy nor any of its employees shall be liable for any losses or damages with respect to or resulting from the user of, or the inability to use, any information, product, process or apparatus discussed in this work.